

TECHNICAL SPECIFICATIONS

CLAYTON STEAM GENERATORS:

- * **SAVE FUEL**
The unique counter flow, controlled flow design provides higher fuel to steam efficiencies than traditional boilers.
- * **ARE SAFE FOR PERSONNEL & EQUIPMENT**
The Clayton units inherently eliminate the potential for hazardous steam explosions due to their smaller physical size and low water volume.
- * **PROVIDE RAPID RESPONSE**
With low water volume and physical size, Clayton units can respond very quickly to load changes
- * **PROVIDE FAST START-UP AND LOAD RESPONSE**
The units will provide full output from a cold start within ten minutes, without thermal stress.
- * **ARE COMPACT AND LIGHTWEIGHT**
The Clayton design typically occupies one-third of the floor space and is 75% lighter than a conventional boiler.
- * **ENSURE HIGH QUALITY STEAM**
Provide greater than 99.5% quality steam.
- * **AFFORD FUEL VERSATILITY**
Natural gas, propane, light or heavy oil burners are available or in combination.
- * **HAVE ADVANCED CONTROLS**
Programmable Logic Controllers (PLC) are standard for accurate and reliable operation.
- * **ARE AVAILABLE WITH LOW NO_x**
Industry leading Low NO_x burners are available to meet strict environmental regulations.
- **ARE BACKED BY** *Fast, Expert Factory-Direct service that is available 24 hours per day throughout the U.S., Canada, Mexico, Europe, Asia and service distributors worldwide.*



MODEL E604
STEAM GENERATOR
600 BHP

CLAYTON STEAM GENERATOR

SPECIFICATIONS

MODEL E604

	MODEL E604 Standard	MODEL SE604 with Super Economizer	MODEL EG604-FMB with Low NOx Burner	MODEL SEG604-FMB with Low NOx Burner and Super Economizer
BOILER HORSEPOWER	600	600	600	600
HEAT INPUT, BTU/hr	24,198,795	23,354,651	NA	NA
Oil	24,493,902	23,629,412	24,796,296	23,629,412
Gas	20,085,000	20,085,000	20,085,000	20,085,000
NET HEAT OUTPUT, BTU/hr				
EQUIVALENT OUTPUT (from and at 212°F feedwater and 0 PSIG steam)	20,700 lbs/hr	20,700 lbs/hr	20,700 lbs/hr	20,700 lbs/hr
DESIGN PRESSURE (see note 1)	65 - 500 PSIG	65 - 500 PSIG	65 - 500 PSIG	65 - 500 PSIG
STEAM OPERATING PRESSURE (determined by design pressure)	60 - 450 PSIG	60 - 450 PSIG	60 - 450 PSIG	60 - 450 PSIG
OIL CONSUMPTION	172.1 gph	166.1 gph	NA	NA
at maximum steam output (see note 2)				
GAS CONSUMPTION	24,494 cfm	23,629 cfm	24,796 cfm	23,629 cfm
at maximum steam output (see note 3)				
BURNER CONTROLS	5 to 1 Turndown	5 to 1 Turndown	4 to 1 Turndown	4 to 1 Turndown
modulating				
EFFICIENCY				
oil-fired efficiency %	83%	86%	NA	NA
gas-fired efficiency %	82%	85%	81%	85%
ELECTRIC MOTORS, HP	Blower Pump	Blower Pump	Blower Pump Cooling	Blower Pump Cooling
design pressure 15-300 psig	40 30	40 30	60 30 7.5	60 30 7.5
design pressure 301-500 psig	40 30	40 30	60 30 7.5	60 30 7.5
ELECTRIC FLA, based on 460 V (see note 4)				
design pressure 15-300 psig	103	103	122	122
design pressure 301-500 psig	103	103	122	122
GAS SUPPLY PRESSURE REQUIRED	5 to 10 psig	5 to 10 psig	5 to 10 psig	5 to 10 psig
ATOMIZING AIR REQUIRED (see note 5)				
Capacity	30 scfm	30 scfm	NA	NA
Minimum pressure	70 psig	70 psig	NA	NA
AIR SUPPLY REQUIRED (FMB -see note 6)	N/A	N/A	5 scfm @ 3 to 150 psig	5 scfm @ 3 to 150 psig
WATER SUPPLY REQUIRED	3,180 gph	3,180 gph	3,180 gph	3,180 gph
HEATING SURFACE	1,253 sq.ft.	1,548 sq.ft.	1,253 sq.ft.	1,548 sq.ft.
EXHAUST STACK DIAMETER, o.d.	31.75 in.	31.75 in.	31.75 in.	31.75 in.
APPROXIMATE OVERALL DIMENSIONS				
length	133 in.	133 in.	156 in.	156 in.
width	131 in.	131 in.	142 in.	142 in.
height	181 in.	207 in.	185 in.	211 in.
WEIGHT				
installed - wet	21,448 lbs	27,230 lbs	21,748 lbs	27,530 lbs
shipping	17,980 lbs	23,170 lbs	18,280 lbs	23,470 lbs
FW pump skid	2,200 lbs	2,200 lbs	2,200 lbs	2,200 lbs

1) Design pressures are available up to 3000 psig. Consult factory for details.

2) Based on No. 2 fuel oil with a High Heat Value (HHV) of 140,600 BTU/Gal.

3) Based on Natural Gas with a High Heat Value (HHV) of 1,000 BTU/Ft.³

4) Continuous running. For 575 V multiply by 0.8; for 380 V multiply by 1.1; for 230 V multiply by 2.0; for 208 V multiply by 2.2.

5) Atomizing air required for oil burner.

6) Compressed air required for FMB.

The description and specifications shown were in effect at the time this publication was approved for printing. Clayton Industries, whose policy is one of continuous improvement, reserves the right to discontinue models, or change specifications or design, without notice.



World Headquarters
17477 Hurley Street
City of Industry, CA 91744
800.423.4585 tel • 626.435.0180 fax
email: sales@claytonindustries.com
www.claytonindustries.com

Europe, Africa & Middle East Headquarters
Rijksweg 30 • B-2880 Bornem, Belgium
32.3.890.5700 tel • 32.3.890.5701 fax
email: sales@clayton.be

Latin America Headquarters
Manuel L. Stampa 54 • Nueva Industrial Vallejo
Mexico D.F., 07700 Mexico
Toll Free: 01.800.888.4422 • (55)55.86.51.00 tel
(55)55.86.23.00 fax • email: claytonmexico@clayton.com.mx
www.claytonmexico.com.mx

ATLANTA • BOSTON • CHICAGO • CINCINNATI • CLEVELAND • DALLAS • DETROIT • KANSAS CITY • NEW YORK/NEW JERSEY • SAN FRANCISCO

Clayton Deutschland GmbH
Clayton Thermal Products Ltd (UK)

Clayton Scandinavia A.S.
Clayton Nederland B.V.

Clayton de France S.A.R.L.
Clayton Sales & Service Canada

World Leaders in Precision Steam Generators, Fluid Heaters, Heat Recovery Systems and Customer Service