

Specifications

*Advanced Steam Boiler Technology
that is Safe, Efficient and Reliable*

CLAYTON FLUID HEATERS OFFER:

- **COMPACT SIZE**

Clayton steam generators will normally fit in any available area while also reducing construction costs on new building installations.

- **FUEL EFFICIENT**

High efficiency which is inherent with the clayton design translates into lower operating costs and improved overall system operation

- **RESPONSIVE**

Very rapid response to changing steam loads. Clayton steam generator will automatically modulate to match your steam load profile while maintaining system steam pressure

- **SAFE**

Our once through design eliminates the possibility of a steam or water side explosion. The Clayton steam generator is simply the safest steam boiler on the market.

- **LESS WATER WASTE**

Clayton's design concentrates TDS blow down significantly which reduces wasted fuel, water and chemical costs.

- **FAST START**

Full steam pressure and output in minutes from a cold start-up saves fuel and labor cost over conventional designs. Eliminates wasted fuel from idling.

- **AUTOMATIC**

Operation is automatically controlled and the Clayton steam generator can be started from a single switch or remotely using an automatic start option.

- **LOW WEIGHT**

The relatively light weight means that all sizes of Clayton steam generators can be easily moved and installed even in areas with limited structural support.

- **RELIABLE**

Reliability of the Clayton steam generator is field proven and unsurpassed. This results in greatly reduced maintenance and attendance.

- **HIGH QUALITY STEAM**

Steam Quality in excess of 99.5% dry is assured at all times. This is the highest steam quality of any competitive design. Less water and impurities further increase your energy efficiency.

MODEL E204-DZ FLUID HEATER 200 BHP



Clayton
INNOVATIVE STEAM SOLUTIONS

S
A
V
E
S

F
U
E
L

*

S
A
V
E
S

S
P
A
C
E

*

S
A
V
E
S

T
I
M
E

*

S
A
V
E
S

M
O
N
E
Y

SPECIFICATIONS

MODEL E204

	MODEL E204 Standard	MODEL SE204 with Super Economizer	MODEL E204-FGR with Flue Gas Recirculation	MODEL SE204-FGR with Flue Gas Recirculation and Super Economizer
BOILER HORSEPOWER	200	200	200	200
HEAT INPUT, BTU/hr				
Oil	8,066,265	7,784,884	8,066,265	7,784,884
Gas	8,164,634	7,876,471	8,164,634	7,876,471
NET HEAT OUTPUT, BTU/hr	6,695,000	6,695,000	6,695,000	6,695,000
EQUIVALENT OUTPUT (from and at 212°F feedwater and 0 PSIG steam)	6,900 lbs/hr	6,900 lbs/hr	6,900 lbs/hr	6,900 lbs/hr
DESIGN PRESSURE (see note 1)	15 - 500 psig	15 - 500 psig	15 - 500 psig	15 - 500 psig
STEAM OPERATING PRESSURE (determined by design pressure)	13 - 450 psig	13 - 450 psig	13 - 450 psig	13 - 450 psig
OIL CONSUMPTION at maximum steam output (see note 2)	57.4 gph	55.4 gph	57.4 gph	55.4 gph
GAS CONSUMPTION at maximum steam output (see note 3)	8,165 cfm	7,876 cfm	8,165 cfm	7,876 cfm
BURNER CONTROLS				
modulating	5 to 1 Turndown	5 to 1 Turndown	4 to 1 Turndown	4 to 1 Turndown
EFFICIENCY				
oil-fired efficiency %	83%	86%	83%	86%
gas-fired efficiency %	82%	85%	82%	85%
ELECTRIC MOTORS, HP (see note 4)	Blower Pump	Blower Pump	Blower Pump Cooling	Blower Pump Cooling
design pressure 15-300 psig	10 7.5	10 7.5	10 7.5 5	10 7.5 5
design pressure 301-500 psig	10 10	10 10	10 10 5	10 10 5
ELECTRIC FLA, based on 460 V (see note 5)				
design pressure 15-300 psig	32	32	39	39
design pressure 301-500 psig	35	35	42	42
GAS SUPPLY PRESSURE REQUIRED	5 to 10 psig	5 to 10 psig	5 to 10 psig	5 to 10 psig
ATOMIZING AIR REQUIRED (see note 6)				
Capacity	25 scfm	25 scfm	25 scfm	25 scfm
Minimum pressure	70 psig	70 psig	70 psig	70 psig
AIR SUPPLY REQUIRED (FMB -see note 7)	N/A	N/A	N/A	N/A
WATER SUPPLY REQUIRED	1,060 gph	1,060 gph	1,060 gph	1,060 gph
HEATING SURFACE	473 sq.ft.	610 sq.ft.	473 sq.ft.	610 sq.ft.
EXHAUST STACK CONNECTION, o.d.	18 in.	18 in.	18 in.	18 in.
APPROXIMATE OVERALL DIMENSIONS				
length	114 in.	114 in.	140	140
width	93 in.	93 in.	113	113
height	102 in.	121 in.	126	145
WEIGHT				
installed - wet	8,427 lbs	9,641 lbs	8,627 lbs	9,841 lbs
shipping	7,410 lbs	8,390 lbs	7,610 lbs	8,590 lbs
FW pump skid	1,050 lbs	1,050 lbs	1,050 lbs	1,050 lbs

1) Design pressures are available up to 3000 psig. Consult factory for details.

2) Based on No. 2 fuel oil with a High Heat Value (HHV) of 140,600 BTU/Gal.

3) Based on Natural Gas with a High Heat Value (HHV) of 1,000 BTU/Ft.³

4) Oil fired units also use a separate motor driven fuel oil pump - 1/3 HP

5) Continuous running. For 575 V multiply by 0.8; for 380 V multiply by 1.1; for 230 V multiply by 2.0; for 208 V multiply by 2.2.

6) Atomizing air required for oil burner.

7) Compressed air required for FMB.

The description and specifications shown were in effect at the time this publication was approved for printing. Clayton Industries, whose policy is one of continuous improvement, reserves the right to discontinue models, or change specifications or design, without notice.



World Headquarters
17477 Hurley Street
City of Industry, CA 91744
800.423.4585 tel • 626.435.0180 fax
email: sales@claytonindustries.com
www.claytonindustries.com

Europe, Africa & Middle East Headquarters
Rijksweg 30 • B-2880 Bornem, Belgium
32.3.890.5700 tel • 32.3.890.5701 fax
email: sales@clayton.be

Latin America Headquarters
Manuel L. Stampa 54 • Nueva Industrial Vallejo
Mexico D.F., 07700 Mexico
Toll Free: 01.800.888.4422 • (55)55.86.51.00 tel
(55)55.86.23.00 fax • email: claytonmexico@clayton.com.mx
www.claytonmexico.com.mx

ATLANTA • BOSTON • CHICAGO • CINCINNATI • CLEVELAND • DALLAS • DETROIT • KANSAS CITY • NEW YORK/NEW JERSEY • SAN FRANCISCO

Clayton Deutschland GmbH
Clayton Thermal Products Ltd (UK)

Clayton Scandinavia A.S.
Clayton Nederland B.V.

Clayton de France S.A.R.L.
Clayton Sales & Service Canada

World Leaders in Precision Steam Generators, Fluid Heaters, Heat Recovery Systems and Customer Service