

Specifications

*Advanced Steam Boiler Technology
that is Safe, Efficient and Reliable*

CLAYTON STEAM GENERATORS OFFER:

- **COMPACT SIZE**

Clayton steam generators will normally fit in any available area while also reducing construction costs on new building installations.

- **FUEL EFFICIENT**

High efficiency which is inherent with the Clayton design translates into lower operating costs and improved overall system operation

- **RESPONSIVE**

Very rapid response to changing steam loads. Clayton steam generator will automatically modulate to match your steam load profile while maintaining system steam pressure

- **SAFE**

Our once through design eliminates the possibility of a steam or water side explosion. The Clayton steam generator is simply the safest steam boiler on the market.

- **LESS WATER WASTE**

Clayton's design concentrates TDS blow down significantly which reduces wasted fuel, water and chemical costs.

- **FAST START**

Full steam pressure and output in minutes from a cold start-up saves fuel and labor cost over conventional designs. Eliminates wasted fuel from idling.

- **AUTOMATIC**

Operation is automatically controlled and the Clayton steam generator can be started from a single switch or remotely using an automatic start option.

- **LOW WEIGHT**

The relatively light weight means that all sizes of Clayton steam generators can be easily moved and installed even in areas with limited structural support.

- **RELIABLE**

Reliability of the Clayton steam generator is field proven and unsurpassed. This results in greatly reduced maintenance and attendance.

- **HIGH QUALITY STEAM**

Steam Quality in excess of 99.5% dry is assured at all times. This is the highest steam quality of any competitive design. Less water and impurities further increase your energy efficiency.

MODEL E704 STEAM GENERATOR 700 BHP



S
A
V
E
S

F
U
E
L

*

S
A
V
E
S

S
P
A
C
E

*

S
A
V
E
S

T
I
M
E

*

S
A
V
E
S

M
O
N
E
Y

SPECIFICATIONS

MODEL E704

	MODEL E704 Standard	MODEL SE704 with Super Economizer	MODEL EG704-FMB with Low NOx Burner	MODEL SEG704-FMB with Low NOx Burner and Super Economizer
BOILER HORSEPOWER	700	700	700	700
HEAT INPUT, BTU/hr	Oil 28,231,928 Gas 28,576,220	27,247,093 27,567,647	NA 28,929,012	NA 27,567,647
NET HEAT OUTPUT, BTU/hr	23,432,500	23,432,500	23,432,500	23,432,500
EQUIVALENT OUTPUT (from and at 212°F feedwater and 0 PSIG steam)	24,150 lbs/hr	24,150 lbs/hr	24,150 lbs/hr	24,150 lbs/hr
DESIGN PRESSURE (see note 1)	65 - 500 psig	65 - 500 psig	65 - 500 psig	65 - 500 psig
STEAM OPERATING PRESSURE (determined by design pressure)	60 - 450 psig	60 - 450 psig	60 - 450 psig	60 - 450 psig
OIL CONSUMPTION at maximum steam output (see note 2)	200.8 gph	193.8 gph	NA	NA
GAS CONSUMPTION at maximum steam output (see note 3)	28,576 cfm	27,568 cfm	28,929 cfm	27,568 cfm
BURNER CONTROLS				
modulating	5 to 1 Turndown	5 to 1 Turndown	4 to 1 Turndown	4 to 1 Turndown
EFFICIENCY				
oil-fired efficiency %	83%	86%	NA	NA
gas-fired efficiency %	82%	85%	81%	85%
ELECTRIC MOTORS, HP (see note 4)	Blower Pump	Blower Pump	Blower Pump Cooling	Blower Pump Cooling
design pressure 15-300 psig	60 40	60 40	75 40 7.5	75 40 7.5
design pressure 301-500 psig	60 40	60 40	75 50 7.5	75 50 7.5
ELECTRIC FLA, based on 460 V (see note 5)				
design pressure 15-300 psig	155	155	190	190
design pressure 301-500 psig	155	155	204	204
GAS SUPPLY PRESSURE REQUIRED	5 to 10 psig	5 to 10 psig	5 to 10 psig	5 to 10 psig
ATOMIZING AIR REQUIRED (see note 6)				
Capacity	30 scfm	30 scfm	N/A	N/A
Minimum pressure	70 psig	70 psig	N/A	N/A
AIR SUPPLY REQUIRED (FMB -see note 7)	N/A	N/A	5 scfm @ 3 to 150 psig	5 scfm @ 3 to 150 psig
WATER SUPPLY REQUIRED	3,710 gph	3,710 gph	3,710 gph	3,710 gph
HEATING SURFACE	1,523 sq.ft.	1,701 sq.ft.	1,523 sq.ft.	1,701 sq.ft.
EXHAUST STACK CONNECTION, o.d.	36 in.	36 in.	36 in.	36 in.
APPROXIMATE OVERALL DIMENSIONS				
length	141 in.	141 in.	160 in.	160 in.
width	140 in.	140 in.	149 in.	149 in.
height	205 in.	215 in.	205 in.	215 in.
WEIGHT				
installed - wet	28,535 lbs	32,244 lbs	28,835 lbs	32,544 lbs
shipping	24,500 lbs	27,800 lbs	24,800 lbs	28,100 lbs
FW pump skid	2,400 lbs	2,400 lbs	2,400 lbs	2,400 lbs

1) Design pressures are available up to 3000 psig. Consult factory for details.

2) Based on No. 2 fuel oil with a High Heat Value (HHV) of 140,600 BTU/Gal.

3) Based on Natural Gas with a High Heat Value (HHV) of 1,000 BTU/Ft.³

4) Oil fired units also use a separate motor driven fuel oil pump - 3/4 HP

5) Continuous running. For 575 V multiply by 0.8; for 380 V multiply by 1.1; for 230 V multiply by 2.0; for 208 V multiply by 2.2

6) Atomizing air required for oil burner.

7) Compressed air required for FMB.

The description and specifications shown were in effect at the time this publication was approved for printing. Clayton Industries, whose policy is one of continuous improvement, reserves the right to discontinue models, or change specifications or design, without notice.



World Headquarters
17477 Hurley Street
City of Industry, CA 91744
800.423.4585 tel • 626.435.0180 fax
email: sales@claytonindustries.com
www.claytonindustries.com

Europe, Africa & Middle East Headquarters
Rijksweg 30 • B-2880 Bornem, Belgium
32.3.890.5700 tel • 32.3.890.5701 fax
email: sales@clayton.be

Latin America Headquarters
Manuel L. Stampa 54 • Nueva Industrial Vallejo
Mexico D.F., 07700 Mexico
Toll Free: 01.800.888.4422 • (55)55.86.51.00 tel
(55)55.86.23.00 fax • email: claytonmexico@clayton.com.mx
www.claytonmexico.com.mx

ATLANTA • BOSTON • CHICAGO • CINCINNATI • CLEVELAND • DALLAS • DETROIT • KANSAS CITY • NEW YORK/NEW JERSEY • SAN FRANCISCO

Clayton Deutschland GmbH
Clayton Thermal Products Ltd (UK)

Clayton Scandinavia A.S.
Clayton Nederland B.V.

Clayton de France S.A.R.L.
Clayton Sales & Service Canada

World Leaders in Precision Steam Generators, Fluid Heaters, Heat Recovery Systems and Customer Service